



Hydraulic Power Packs -AHF

JAGODA JPS **PTO Hydraulic Power Packs** is designed for the external hydraulic pump with an oil cooler to power machines and hydraulic devices that require an efficient source of hydraulic drive such as weeder machines connected to the front of the tractor such LUCY orchard weeding machine, agricultural and forestry machines (forage harvesters, spreaders, wrappers, winches, shredders) construction machinery, municipal machines (sweepers, snow plough, sand spreaders), orchard machines, trimmers and many others.

Advantages and benefits:

- In case of tractors have insufficient flow rate, the hydraulic pump is used to supply the working machine directly
- Relieves the tractor's hydraulic system and prevents it from overheating
- Enables the use of implements with different tractors on one frame.
- The PTO shaft does not require as the pump is mounted directly on the tractor PTO.

Technical Specification

Mounting method (Rear)	3-point Linkage CAT 1and CAT 2
Cooler system	oil cooler with thermostat
Max Hydraulic pump flow	67 Litre/minute
Tank Capacity	75 litres
PTO Profile	1.3 / 8 "PTO profile 6 splines
Max Pressure	230 Bar
Min Pressure	190 Bar
PTO Rotation	220-540 rpm
Width	970 mm
Height	1450 mm
Length	550 mm
Weight	~ 150 kg (+ 60 kg Oil)